



OPAL ACRYLIC LIGHT DIFFUSING SHEET

Lumaire Wayfinding



3 YEARS WARRANTY

APPLICATIONS

Airport
 Bus station
 Train station
 Wayfinding

FEATURES

- Frame thickness is just 15mm (single or double-sided)
- Brightness up to 11000lx on the surface depending on size
- Single or double sided, curved
- Low power consumption
- MILKY plexiglas 2mm
- Oracal PVC film

TECHNICAL SPECIFICATIONS

MAIN MATERIAL
 Clear acrylic (PMMA)

LUMINOUS EFFICIENCY
 up to 160lm/W

MAXIMUM SIZE
 2450 x 1250 mm

POWER SUPPLY
 DC 12V / 24V / CC Adaptor

LIGHT TRANSMISSION
 93%

IP RATING
 IP 20

LIFETIME
 > 50,000 hours

WORKING VOLTAGE
 DC 12V / DC 24V / DC CC

FRAME THICKNESS
 15 mm (single or double-sided)

COLOUR TEMPERATURE
 3000K 4000K 5000K 6500K

OPERATING TEMPERATURE
 -30°C ~ + 40°C

INPUT VOLTAGE
 AC 100 ~ 240V 50/60Hz



Tel: +370 5 212 7244
 Mail: info@lumaire.eu

Web: www.lumaire.eu
 Web: www.leddex.eu

Elektrines str. 8,
 LT-03150 Vilnius, Lithuania