



ULTRA THIN-PERFECT BASIC DESIGN

## Lumaire Basic



3 YEARS WARRANTY

### APPLICATIONS

POS Display  
Signage  
Advertising  
Trade fairs  
Retail  
Interior design  
Hotels

### FEATURES

- Thickness is just 5mm (8 mm with heat sink)
- Brightness up to 11000lx on the surface depending on size
- Single or double sided, curved and custom shape options
- Low power consumption
- Wide application possibilities, from interior design to signage
- OPAL front cover 2mm, optional

### TECHNICAL SPECIFICATIONS

**MAIN MATERIAL**  
Clear acrylic (PMMA)

**LUMINOUS EFFICIENCY**  
up to 160lm/W

**MAXIMUM SIZE**  
2450 x 1250 mm

**POWER SUPPLY**  
DC 12V / 24V / CC Adaptor

**LIGHT TRANSMISSION**  
93%

**COLOUR TEMPERATURE**  
3000K 4000K 5000K 6500K

**LIFETIME**  
> 50,000 hours

**WORKING VOLTAGE**  
DC 12V / DC 24V / DC CC

**THICKNESS**  
5mm acrylic, 8mm including heat sink

**IP RATING**  
IP 20

**OPERATING TEMPERATURE**  
-30°C ~ + 40°C

**INPUT VOLTAGE**  
AC 100 ~ 240V 50/60Hz

