



ULTRA THIN-PERFECT BASIC DESIGN

Lumaire Basic



3 YEARS WARRANTY

APPLICATIONS

POS Display
Signage
Advertising
Trade fairs
Retail
Interior design
Hotels

FEATURES

- Thickness is just 5mm (8 mm with heat sink)
- Brightness up to 11000lx on the surface depending on size
- Single or double sided, curved and custom shape options
- Low power consumption
- Wide application possibilities, from interior design to signage
- OPAL front cover 2mm, optional

TECHNICAL SPECIFICATIONS

MAIN MATERIAL
Clear acrylic (PMMA)

LUMINOUS EFFICIENCY
up to 160lm/W

MAXIMUM SIZE
2450 x 1250 mm

POWER SUPPLY
DC 12V / 24V / CC Adaptor

LIGHT TRANSMISSION
93%

COLOUR TEMPERATURE
3000K 4000K 5000K 6500K

LIFETIME
> 50,000 hours

WORKING VOLTAGE
DC 12V / DC 24V / DC CC

THICKNESS
5mm acrylic, 8mm including heat sink

IP RATING
IP 20

OPERATING TEMPERATURE
-30°C ~ + 40°C

INPUT VOLTAGE
AC 100 ~ 240V 50/60Hz



Tel: +370 5 212 7244
Mail: info@lumaire.eu

Web: www.lumaire.eu
Web: www.leddex.eu

Elektrines str. 8,
LT-03150 Vilnius, Lithuania